

How to change: Mercedes W203 engine oil and filter – replacement guide

 VIDEO TUTORIAL

Important!

This replacement procedure can be used for:
MERCEDES-BENZ C-CLASS (W203) C 200 Kompressor (203.045), MERCEDES-BENZ C-CLASS Coupe (CL203) C 200 Kompressor (203.745), MERCEDES-BENZ C-CLASS T-Model (S203) C 200 Kompressor (203.245)

The steps may slightly vary depending on the car design.



REPLACEMENT: ENGINE OIL AND FILTER – MERCEDES W203. LIST OF THE TOOLS YOU'LL NEED:



- Oil filter cup socket 65/67-14f
- Drive socket # 8
- Drive socket # 13
- Ratchet wrench
- Torque wrench
- Flat screwdriver
- Oil drain pan
- Funnel
- Microfibre towel
- Fender cover

AUTODOC recommends:

- Replace the oil filter every time when changing motor oil.
- All work should be done with the engine stopped.
- Wear gloves to prevent contact with hot liquid.

REPLACEMENT: ENGINE OIL AND FILTER – MERCEDES W203. USE THE FOLLOWING PROCEDURE:

1



Open the hood.

2



Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.

3



Remove the engine cover.

AUTODOC recommends:

- Raise the engine cover, holding it on two sides simultaneously.

4

Clean the oil filter housing cap.

5



Unscrew the filter housing cap together with the old filter element. Use the 76-14F socket. Use a ratchet wrench.

6



Prepare a container for the old oil filter.

7



Remove the filter element from the filter housing. Put the old filter cartridge in the container.

8



Cover the oil filter housing with a microfibre towel to prevent dirt and foreign objects from getting into the system.

9



Lift the car using a jack or place it over an inspection pit.

Replacement: engine oil and filter – Mercedes W203. Tip from AUTODOC:

- The vehicle must be on even keel, and if it is at an angle, the drain plug must be at the lowest point.

10



Unscrew the oil filler plug.




11



Undo the fasteners of the oil pan lower cover. Use a drive socket #8. Use a ratchet wrench.

12




Remove the oil pan cover (2 pieces).

13



Put a waste oil container with at least 8 l capacity under the drainage hole.

14



Unscrew the drain plug. Use a drive socket #13. Use a ratchet wrench.

15



Drain the used oil.

Replacement: engine oil and filter – Mercedes W203. Tip from AUTODOC experts:


- Caution! The oil may be hot.

16




Detach the oil filter from the filter cover.

17



Remove the oil filter cover O-ring. Use a flat screwdriver.

18



Install a new O-ring to its mounting seat on the filter cover.

19



Install the new oil filter to the mounting seat on the filter cover.

Please note!


- Make sure to install the filter correctly. Don't mix up the sides of the part.
- Wait until the oil has completely drained from the drainage hole.

20



Clean the area of the oil pan drainage hole.

21




Screw in the new drainage plug and tighten it. Use a drive socket #13. Use a torque wrench. Tighten it to 30 Nm torque.

22



Reinstall the oil pan lower cover (2 pieces).

23




Tighten the fasteners of the oil pan lower cover. Use a drive socket #8. Use a ratchet wrench.

24




Lower the car.

25



Lubricate the rubber seal of the new filter with a little amount of fresh oil.

26



Remove the microfibre towel from the oil filter housing.

27



Screw the new filter into its place.

28



Screw the cap. Use the 76-14F socket. Use a torque wrench. Tighten it to 25 Nm torque.

29



Unscrew the oil filler plug. Insert the funnel.

30




Pour oil into the engine through the filler. Required amount of oil: 7 l.

Replacement: engine oil and filter – Mercedes W203. AUTODOC experts recommend:

- Use the oil recommended by the manufacturer.

31




Check the oil level using the dipstick. Top up oil if necessary.

Please note!


- The oil level should be between the Min and Max marks.

32



Tighten the oil filler cap.

33



Run the engine for a few minutes. After the oil pressure warning light goes out, stop the engine.

34



Check the oil level 5 minutes after the stop of the engine operation using a dipstick and add oil if necessary.

Please note!

- The oil level should be between the Min and Max marks.
- Make sure that the oil filler cap is properly tightened.
- Check the threaded plug of the drainage hole and the oil filter seal for tightness. If necessary, carefully tighten them up.

35



Install the engine cover and secure it.

36

Remove the fender protection cover. Close the hood.

Replacement: engine oil and filter – Mercedes W203. Tip:

- Note that oil pressure warning light, which indicates insufficient pressure in the lubrication system, may be on for a longer time than usual. After a few seconds, the oil will fill all the channels, and the light will go out.
- To protect the environment from pollution, be sure to dispose of the used filters at special collection points.

DID YOU FIND THESE INSTRUCTIONS HELPFUL?

YES

NO



BECOME A MEMBER OF AUTODOC CLUB!

AUTODOC — TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR





BUY SPARE PARTS FOR MERCEDES



OIL FILTERS: A WIDE SELECTION



CHOOSE CAR PARTS FOR MERCEDES W203



OIL FILTER FOR MERCEDES: BUY NOW







Disclaimer:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AutoDoc shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AutoDoc shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AutoDoc shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AutoDoc strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.